

# SAFETY DATA SHEET

## A.W.F. FLEXIBLE RUBBER 80 EG BASE

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name	A.W.F. Flexible Rubber 80 EG Base
Supplier	A.W.F. SMS Ltd
Address	Unit I D Brymau 3 Estate River Lane Saltney Chester, CH4 8RQ
Phone Number	01244 - 677833
Fax Number	01244 - 677844

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Substance/preparation  
DIETHYLTOLUENEDIAMINE

CAS number	% by weight	EC number	Classification
068479-98-1	<2.5%	270-877-4	Xn; R21/22, 48/22, Xi; R36, N;R50/53

See section 16 for the full text of the R-phrases declared above  
Occupational exposure limits, if available, are listed in section 8.

### 3. HAZARDS IDENTIFICATION

The preparation is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification R52/53

Human health hazards Not classified.

Environmental hazards Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

See section 11 for more detailed information on health effects and symptoms.

### 4. FIRST AID MEASURES

#### Ingestion

Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If potentially dangerous quantities of this material have been swallowed, call a physician immediately

#### Skin contact

Wash contaminated skin with soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse. Get medical attention if irritation occurs.

continued on page 2

continued from page 1

Eye contact Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.

See section 11 for more detailed information on health effects and symptoms.

## **5. FIRE-FIGHTING MEASURES**

Extinguishing media In case of fire, use water spray (fog), foam, dry chemical or CO<sub>2</sub>. Do not use water jet.

Special exposure hazards No specific hazard.

Hazardous thermal decomposition products

In a fire, the following may be released: carbon oxides (CO, CO<sub>2</sub>) nitrogen oxides (NO, NO<sub>2</sub> etc.)

Protection of fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## **6. ACCIDENTAL RELEASE MEASURES**

Personal precautions Immediately contact emergency personnel. Use suitable protective equipment (section 8).

Environmental precautions Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Methods for cleaning up If emergency personnel are unavailable, contain spilt material. For small spills, add absorbent (soil may be used in the absence of other suitable materials), scoop up material and place in a sealable, liquid-proof container for disposal. For large spills, dyke spilt material or otherwise contain it to ensure runoff does not reach a waterway. Place spilt material in an appropriate container for disposal.

## **7. HANDLING AND STORAGE**

Handling

Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

Storage

Keep container tightly closed. Store in original sealed containers at temperatures between 5° and 30°C.

## **8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

Exposure controls

Respiratory protection

A respirator is not needed under normal and intended conditions of product use.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. >8 hours (breakthrough time)

continued on page 3

continued from page 2

#### Eye protection

Safety glasses. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

Skin protection Protective clothing.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid. (Viscous liquid. Colour)	Odour	Faint odour.
pH	Not applicable.	Boiling point	>100°C (212°F)
Flash point	Closed cup: >100°C (212°F).	Flammability	Non-flammable.
Explosion limits	Not available.	Oxidising properties	Not available.
Vapour pressure	Not available.	Relative density	1.2 g/cm <sup>3</sup>
Solubility	Insoluble in cold water.	Vapour density	Not available.
Evaporation rate	Not available.	Octanol/water	Not available.
(butyl acetate = 1)		partition coefficient	
Auto-ignition temperature	>400°C (752°F)	Melting point	Not available.

### 10. STABILITY AND REACTIVITY

#### Stability

The product is stable.

#### Conditions to avoid

None identified.

#### Materials to avoid

Strong oxidising materials strong acids alcohols Amines Hazardous decomposition products In a fire, the following may be released: carbon oxides (CO, CO<sub>2</sub>) nitrogen oxides (NO, NO<sub>2</sub> etc.)

### 11. TOXICOLOGICAL INFORMATION

#### Potential acute health effects

Inhalation No known significant effects or critical hazards.

Ingestion No known significant effects or critical hazards.

Skin contact No known significant effects or critical hazards.

Eye contact No known significant effects or critical hazards.

#### Acute toxicity

Ingredient name	Test	Result	Route	Species
DIETHYLTOLUENEDIAMINE	LD50	>507 mg/kg	Oral	Rat
	LD50	700 mg/kg	Dermal	Rabbit

#### Potential chronic health effects

Carcinogenicity No carcinogenic effect

Mutagenicity No mutagenic effect

Reproductive toxicity No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

Inhalation No known significant effects or critical hazards.

Ingestion No known significant effects or critical hazards.

Skin No known significant effects or critical hazards.

#### Additional information

No components of this material are listed as carcinogens by OSHA, NTP, ACGIH or IARC.

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity data

Ingredient name	Species	Period	Result
DIETHYLTOLUENEDIAMINE	Daphnia (EC50)	48 hours	0.5 mg/l
	Fish (LC50)	96 hours	203 mg/l

### Persistence/degradability

Ingredient name	Aquatic half-life	Photolysis	Biodegradability
AWF Flexible Rubber 80EG Base	-	-	Not readily

### Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

Mobility Do not allow to enter drains or watercourses.

Other adverse effects Harmful to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

## 13. DISPOSAL CONSIDERATIONS

### Methods of disposal

The generation of waste should be avoided or minimised wherever possible. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

### Hazardous waste

The classification of the product may meet the criteria for a hazardous waste.

## 14. TRANSPORT INFORMATION

International transport regulations

Additional information This preparation is not classified as dangerous according to international transport regulations (ADR/RID, IMDG or ICAO/IATA).

## 15. REGULATORY INFORMATION

EU regulations

Risk phrases R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases S26- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S28- After contact with skin, wash immediately with plenty of soap and water. S29- Do not empty into drains.

Product use Classification and labelling have been performed according to EU Directives 67/548/EEC and 1999/45/EC (including amendments) and the intended use.

- Consumer applications.

Other EU regulations

EU statistical classification 39072021  
(Tariff Code)

National regulations

United States

SARA 313 toxic chemical notification and release reporting No products were found.

Germany Hazard class for water 2

## 16. OTHER INFORMATION

Full text of R-phrases referred to in sections 2 and 3 - Europe

R21/22- Harmful in contact with skin and if swallowed. R48/22- Harmful: danger of serious damage to health by prolonged exposure if swallowed. R36- Irritating to eyes. R50/53- Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Full text of classifications referred to in sections 2 and 3 - Europe

Xn - Harmful

Xi - Irritant

N - Dangerous for the environment.

Further information

Conforms to EU Directive 91/155/EEC, as amended by 2001/58/EC

Canada - This product has been classified according to the hazard criteria of the CPR and the

MSDS contains all the information required by the CPR.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user.

All materials may present unknown hazards and should be used with caution.

Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of issue 11/01/2007