

A.W.F. WEATHERGUARD

Weather-Guard is a two coat, single pack system designed for the external protection of most building substrates which includes concrete, plaster, brick, asbestos, cement-rendering etc.

Available in 5ltr and 25ltr containers.



All surfaces should be clean, dry and free from other contamination. Any areas of moss or lichen growth should be cleaned then treated with A.W.F. Fungal Wash.



N/A.



Touch dry: 30 mins at 20 °C
Minimum overcoating: 2 hours at 20 °C
Maximum overcoating: Indefinite.



N/A.

APPLICATION DETAILS



A.W.F. Weather-Guard can be applied by brush. Use a good quality brush. Weather-Guard should be worked into the surface to ensure complete coverage. Weather-Guard can be thinned with a maximum of 10% clean water.



4 m² per litre at 150 microns.
2.64 m² per litre at 250 microns -Two coats.



5°C
(Must not be used when humidity exceeds 90%)



Indefinite in unopened containers. Stored between 5°C and 30°C.



A.W.F. Weather-Guard is a water based product which does not present any health hazards during normal use.

Notes: Fire Classification

The system conforms to the BS 476 parts 6 and 7 to a class O rating when applied to a non-combustible substrate.

If you have any questions or queries regarding this data sheet or the application of this product, please contact us before you use the product.