

A.W.F AERO PACK FLEXIBLE RUBBER S.P.

Low volatile, high temperature black rubber sealant. Equipped with oxygen sensors and OEM. Approved for engines. Makes an instant leakproof gasket on all engines, seals windcreens mouldings, rubber hose connections and insulates wiring.



Clean surfaces thoroughly using AWF All Purpose Cleaner.



N/A



Touch Dry: 20 mins

Full Cure: 10 – 12 hours




N/A

APPLICATION DETAILS

Depress nozzle to one side and apply a thin even bead to one surface. Wait a few minutes before assembly. For temporary assemblies, apply a light coat of oil to surfaces, then assemble. Clean excess off with a knife or AWF All Purpose Cleaner. After use, depress nozzle to leave about ¼ inch expanding from the nozzle. This will cure and act as a plug which can be removed before next usage.



10 metres at a 6mm bead



N/A



2 years at room temperature



Avoid prolonged breathing of vapours.
Make sure there is adequate ventilation.

A fully detailed Material Safety Data Sheet is available on request.

Chemical Resistance: Oil, Transmission fluid,
Anti-Freeze, Diesel, Lubricants, water and steam.

**General notes: Temp: Resistance between -73°C up to +315°C.
Dielectric strength 500 volts/mm. Used in a large variety of Automotive
Industrial and household applications. Can replace many gaskets e.g. oil
pan, water pump, hose outlets, valve cover, timing gear cover, thermostat
housing. Excellent sealant for Auto windshields, bonding weather strips and
sealing leaks. Insulates electrical wiring, repairs worn rubber parts. Will bond to
glass, wood, metal, ceramic, plastic, rubber, concrete etc.**

If you have any questions or queries regarding this data sheet or the application of this product, please contact us before you use the product.