

A.W.F. UNIVERSAL PRIMER

AWF Universal Primer is a two pack water dispersed epoxy resin system which is an easily applied primer for use with AWF epoxy resin coatings and screeds. It can be applied to newly layed concrete as well as damp or dry mature concrete.



Preparation

All surfaces should be clean, free from laitance, oil, grease or other agents which may impair adhesion. Cleaning techniques depending on surface contamination could be any of the following: acid etching, light mechanical scabbing, blasting, gending, or general degreasing.



Mixing Ratio

AWF Universal Primer is a two part material consisting of a Base and Activator resin. The base should be poured into a suitable container and stirred for 2 – 3 minutes. The activator should be stirred for 2 – 3 minutes then added to the base resin and stirred for at least 4 minutes or until a homogenous mix is obtained.



Curing Time

Drying, Curing times @ 20°C

Initial hardness: 24 hours
Full cure: 7 days




Pot Life

Once you have mixed the Base and Activator together, you have approximately 60 minutes to use the mixed material.

APPLICATION DETAILS.



AWF Universal Primer should be applied to the prepared surface by brush or roller, ensuring a continuous film. Avoid over application of the product as this may cause ponding. Porous surfaces may require two coats.



All equipment must be cleaned immediately after use with AWF Universal Cleaner.



Theoretical coverage rate

4.5kg unit will cover 25 – 30m²
(depending on the porosity of the substrate)



This product should not be used if the temperature or the surface to be coated falls below 10°C



Use within 12 months of purchase.
Store in original sealed containers at temperatures between 5°C (40°F) and 30°C and (86°F).



As long as good practice is observed, AWF Universal Cleaner can be safely used.

Protective gloves should be worn.
Barrier creams should also be used.

A fully detailed Material Safety Data Sheet is available on request

If you have any questions or queries regarding this data sheet or the application of this product, please contact us before you use the product.