

A.W.F ANTI-SEIZE

A.W.F. Anti-Seize is a high performance lubricating compound designed for application to components to assembly to prevent seizure and allow easy dismantling after service. It is based on a unique blend of high temperature oils and soft metallic fillers to produce a compound that has excellent temperature performance and resistant to corrosion or chemical attack.

It has also high resistance to pressure and will resist severe expansion, contraction or vibration.



All areas should be clean, dry and free from contamination. Any contamination should be wiped from the surface using clean cloths.



A.W.F. Anti-Seize is a single component material supplied ready for use which may require stirring prior to use to incorporate any slight separation.



N/A



N/A

APPLICATION DETAILS



A.W.F. Anti-Seize should be applied to all prepared surfaces by brush ensuring complete wetting out of the treated surface. Following application, the treated components can be assembled and any excess Anti-Seize scraped clear or wiped off with a clean dry rag. All equipment should be cleaned immediately after use With A.W.F. Universal Cleaner.

Appearance: Thixotropic Copper Liquid
Volume Solids: 100%
V.O.C.: Nil
Packaging: 0.500kg and 1 kg units.



N/A



Ensure that the surface is above 10°C



Use within 5 years of purchase. Store in original sealed containers at temperatures between 5°C (40°F) and 30°C (86°F).



As long as good practice is observed, AWF Anti-Seize can be safely used.

Protective gloves should be worn during use.

A fully detailed Material Safety Data Sheet is available on request.

If you have any questions or queries regarding this data sheet or the application of this product, please contact us before you use the product.