A.W.F. CLEARSHIELD

AWF Clearshield is a high performance, simple to use non silicone transparent water repellent system designed for application to masonry surfaces. AWF Clearshield is micro-porous, allowing the masonry to breathe and meets the requirements of BS6477:1984 for brickwork and limestone surfaces.




All surfaces should be clean, dry and free from contamination. Any adjacent painted areas such as door and window frames should be protected against contact as AWF Clearshield may cause softening of the paint.



AWF Clearshield is a single component material and should only require stirring prior to use to incorporate any slight separation.



Drying, Curing times at 20° 2 – 4 hours depending on prevailing conditions.



N/A

APPLICATION DETAILS



AWF Clearshield should be applied liberally to the prepared surface using pneumatic spray or a large paint brush. Application should start at the highest point of the surface to be treated allowing excess material to drain down the surface. One coat is sufficient for most surfaces, however on very porous surfaces a second coat should be applied as soon as the first coat is dry. All equipment should be cleaned immediately after use with AWF Universal Cleaner.



Theoretical coverage rate

Whilst it is not possible to provide a theoretical coverage rate. In practice coverage varies between 2 and 4m² per litre (21.5ft² and 43ft² per litre) depending on the porosity of the surface.

<u>Appearance:</u> Clear liquid

Volume solids: 7%

V.O.C.: 783gm/litre



N/A



Use within 5 years of purchase. Store in original sealed containers at temperatures between 10°C (50°F) and 30°C (86°F)



In the wet state AWF Clearshield is flammable. Adequate ventilation should be provided in confined areas.

Undue skin contact should be avoided. Eyes should be protected from splashes by wearing goggles.

A fully detailed Material Safety Data Sheet is available on request

If you have any questions or queries regarding this data sheet or the application of this product, please contact us <u>before</u> you use the product.