

A.W.F. DRAIN CLEANER

AWF Drain Cleaner is a blend of sulphuric acid with special wetting agents and corrosion inhibitors. It is designed to remove all blockages from drains including grease, fat, teabags, cardboard, body waste uric acid and vegetable matter.



Before treating, remove as much water as possible from the drain, sink or toilet to be cleared.



Sinks and drains: Apply ½ litre of Drain Cleaner and allow to stand for 10 minutes, then flush well with water. Repeat if necessary.

Toilet and floor drains: Use ½ litre measures and apply as for sinks and drains.



N/A

APPLICATION DETAILS.

Toilet and U bends – Apply through a length of ½ bore rubber or plastic. Block one end with tissue paper and feed into the drain over the trap. Using a funnel, pour ¼ litre of drain cleaner into the hose. Leave for 5 minutes. If water is not present, add ¼ litre of water, allow to stand for 2 minutes and then flush well.

AWF Drain cleaner cannot be used on aluminium or galvanised metal. It will not harm iron, copper, steel, clay, rubber, plastic, or cement based pipes or septic tanks. **DO NOT MIX WITH ETHER PRODUCTS.**



N/A



N/A



Store in original sealed containers at temperatures between 5°C (40°F) and 30°C (86°F)



As long as good practice is observed AWF Drain Cleaner can be safely used. Protective gloves should be worn during use. This product is given the group classification C. Products in this group all contain mineral acids. They do however differ in the degree of acidity.

A fully detailed Material Safety Data Sheet is available on request

If you have any questions or queries regarding this data sheet or the application of this product, please contact us before you use the product.