

A.W.F. EXTERIOR COATING

A.W.F. Exterior Coating is a high build solvent based modified styrene acrylic resin coating designed as an external decorative and protective finish which is hard wearing and weather resistant.



Satisfactory performance can only be achieved if the substrate is sound, free from dirt and grease and reasonably dry.



N/A



Drying is mainly by evaporation of solvent but because of the thickness of the coating, it may take two or three days to dry.




N/A

APPLICATION DETAILS




Brush

Suitable for the decoration of external substrates including concrete, brickwork, asbestos, cement and rendering. Also suitably primed aluminium and iron work, together with the above mentioned surfaces previously painted with emulsion or oil paints.



Roller

This product should not be used on high density low suction substrates such as glazed bricks, faience tiles and engineering bricks.




Spray



Coverage

Between 50 – 100 sq. metres per 25 litres dependant on substrate and finish



Minimum Cure Temperature

N/A



Not significantly affected over three years, in normal U.K. extremes.



Cleaning

Normal washing, even frequently with detergent water and a soft brush will not affect the coating

Precautions

The paint is flammable. Isolate from sources of heat, naked flames and sparks. Maintain efficient ventilation. Avoid contact with the vapours, which are anaesthetic and irritating to the eyes, nose and throat. Do not breathe the vapour or spray. Avoid physical contact with the paint, which may irritate the skin. In case of splashes to the skin, remove contaminated clothing. Wash thoroughly with soap and water or a proprietary industrial cleaner.

A fully detailed Material Safety Data Sheet is available on request.

If you have any questions or queries regarding this data sheet or the application of this product, please contact us before you use the product.