

A.W.F. INSTANT TARMAc REPAIR

A.W.F. Instant Tarmac Repair is ideal for quick and permanent repairs for pot holes, expansion joints, infilling concrete and is widely used on motorways, airports and roads plus many more applications.



Brush any standing water and loose debris from the hole, cut back edges to a depth of 12mm min. Very dusty areas should be wetted first.



Ready to use from the container.



Instant Tarmac Repair will remain flexible for a few hours although it will form an immediate repair. Curing takes place by compaction and partly by air drying and therefore is dependant upon temperature and weight/volume of traffic. However, during curing Instant Tarmac Repair will not depress, track or pick up.



N/A


APPLICATION DETAILS

Tip the product straight from the container to overfill the hole ensuring that all edges are filled. Compact the material to surrounding level with the back of a shovel or hand tamper. For large areas or deep sections, use a vibrating plate or roller slightly wetting the drum with water.

Instant Tarmac Repair can be used in any weather conditions at temperatures from -45°C to $+65^{\circ}\text{C}$.



N/A



N/A



Approximately 12 months in unopened containers.



Instant Tarmac Repair is non-toxic and non-flammable. Stains on the skin can be removed by a proprietary cleaner. The product can be very tacky, therefore the use of rubber gloves is advised during application.

General Notes: Instant Tarmac Repair is a blend of selected aggregates with a special binding liquid based on selected penetrates, bitumens, resins, and other additives. The product is accepted as a permanent wearing course under B.S. 4987 – 1988.

A fully detailed Material Safety Data Sheet is available on request.

If you have any questions or queries regarding this Data Sheet or the application of this product, please contact us before you use this product.



Mixing Ratio