

A.W.F. SMS Ltd
Unit 1 D, Brymau 3 Estate
River Lane, Saltney
Chester
CH4 8RQ

Tel: 01244 677833
Fax: 01244 677844

E-mail: sales@awf-ltd.com
website: www.awf-ltd.com

PRODUCT SPECIFICATION SHEET

PRODUCT TECHNICAL DATA SHEET : ANTI-VANDAL (ANTI-CLIMB) PAINT

Non drying paint formulated for application to fences and walls to deter intruders/vandals

Viscosity	Thixotropic
Thinner	T7004 (T/4)
Surface preparation	Surfaces must be reasonably clean, dry and free from heavy dust deposits, grease and oil
Film Thickness	Apply to a high thickness by brush
Volatile Organic Content	Typically 250grams/litre
Covering capacity	Approximately 5 sq metres per litre (dependent on film thickness)
Overcoating	Can be applied over previously painted materials. If applying over previous coats of anti-vandal paint then this may have to be scraped off if badly contaminated with dirt
Specific gravity	Typically 0.9
Flash point	> 38°C
Shelf life	2 years, in an unopened, original container from date of manufacture. Storage should be in accordance with the instructions in section 7 of the relevant MSDS
Colours	black
Health & Safety	Before using this product refer to A.W.F. SMS Ltd MSDS HS2