

## **A.W.F PIPE SEAL WITH TEFLON**

Pipe Seal is designed for locking and sealing pipe threads. The vibration loosening of joints is eliminated.

Pipe seal gives an instant low pressure seal which allows systems to be started up without delay.

Pipe seal has gap filling ability and is suitable for use on medium to large threaded fittings.

Its thixotropic nature prevents migration of the product during application.



Ensure parts are clean, dry and free from oil and grease.



N/A - Single Pack



N/A



N/A

## APPLICATION DETAILS

Pipe seal is designed for sealing coarse threaded fittings. Typical applications include:-

Sprinkler systems, Gas pipes, Hydraulic and Pneumatic systems.

Because of Pipesal's anaerobic nature, any excess pipe sealant outside the bond line does not cure and can be flushed through the system without risk of blockage. Pipe sealant replaces pipe tapes and dopes.


## PERFORMANCE CHARACTERISTICS

<u>Strength</u>	<u>Typical Values</u>
Breakloose	5 – 10 N.m
Prevail	3 – 8 N.m
Static shear	6 – 10 N/mm (2)

Tested on M10 mild steel nuts and bolts.



N/A



N/A



Store product out of sunlight in original containers. Storage life approximately 1 year at room temperature. Store product upright in original containers.



Avoid prolonged contact with skin. Wash splashes from skin with soap and water. If splashes enter eyes, flush immediately with water and seek medical advice. A fully detailed Material Safety Data Sheet is available on request.



Greater than 100°

If you have any questions or queries regarding this data sheet or the application of this product, please contact us before you use the product.