

## **A.W.F SAFETY TREAD TAPES**

Fast, effective Anti-slip for most substrates.

The system can be used inside or outside

Ideal for steps, walkways etc.

Durable, Efficient and Effective



A clean dry surface is essential.  
Use All Purpose Cleaner to remove all surface contaminants (paint flakes etc)  
DO NOT use methylated spirits etc as these leave behind a thin, greasy residue.  
**Porous surfaces:** Use AWF H3506 Primer to prevent water attacking the adhesive.  
Apply a thin coat to the cleaned surface using a paint brush.



N/A



Can be traversed immediately, though maximum benefit from the adhesive takes 48 hours.



N/A

## **APPLICATION DETAILS**

Peel back part of the release liner then press the adhesive firmly onto the prepared surface, and slowly keep peeling back the liner while applying the tape.


Try to ensure that the tape is not taut.

**Finish**:- Once applied, press tape down firmly using even pressure (decorating rollers are excellent for this)

We recommend sealing the edges using AWF Edge Fix as this will extend the life of the product. Only use a small amount down the edges, a thin bead.



1 x Roll @ 18.3mtrs long.



Ensure that the surface is above 10°C



Ensure that the material is kept in dry, warm conditions in the original protective packaging.



As long as good practice is observed, AWF Safety Tread Tapes can be safely used.

A fully detailed Material Safety Data Sheet is available on request.

If you have any questions or queries regarding this data sheet or the application of this product, please contact us before you use the product.